

Model: E-350 Cutaway SRW



Fuel Capacity and Engine Highlights

| | | |
|---------------|------------------------------------|---------------------------|
| | | |
| Engine Type | 5.4L Triton® 16-valve Flex Fuel V8 | 6.8L Triton® 20-valve V10 |
| Fuel Capacity | 40/55 gallons | 40/55 gallons |

[Back to Top](#)

Vehicle Highlights

| | |
|--------------------|---|
| Drive Type | 4x2 |
| Transmission | TorqShift® 5-speed automatic overdrive |
| Wheelbase | 138" (E-350 SRW/DRW) |
| | 158" (E-350 SRW/DRW, E-450 DRW) |
| | 176" (E-350 DRW, E-450 DRW) |
| Maximum GVWR Range | 10,050 lbs. to 14,500 lbs. |
| Warranty | Bumper to Bumper: 3 years / 36,000 miles |
| | Powertrain: 5 years / 60,000 miles |
| | Safety Restraint System: 5 years / 60,000 miles |
| | Corrosion (Perforation Only): 5 years / Unlimited miles |
| | Roadside Assistance Program: 5 years / 60,000 miles |

[Back to Top](#)

Exterior Dimensions



| | E-350 Super Duty® Cutaway (SRW) | E-350 Super Duty® Cutaway (DRW) | E-350 Super Duty® Cutaway (DRW) | E-350 Super Duty® Cutaway (DRW) | E-450 Super Duty® Cutaway (DRW) | E-450 Super Duty® Cutaway (DRW) | E-350 Super Duty® Cutaway (SRW) |
|--|------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Wheelbase (in.) | 138 | 138 | 158 | 176 | 158 | 176 | 158 |
| Overall Length (in.) | 241.1 | 241.1 | 261.1 | 261.1 | 261.1 | 261.1 | 261.1 |
| Overall Height (Loaded) (in.) | 80.4 | 80.3 | 80.2 | 80.1 | 80 | 80 | 80.3 |
| Overall Width (in.) | 79.4 | 94.9 | 94.9 | 94.9 | 94.9 | 94.9 | 94.9 |
| Front Track (in.) | 69.4 | 69.4 | 69.4 | 69.4 | 69.4 | 69.4 | 69.4 |
| Rear Track (in.) | 72.1 | 75.4 | 75.4 | 75.4 | 77.7 | 77.7 | 72.1 |
| Cab Length (in.) | 92.5 | 92.5 | 92.5 | 92.5 | 92.5 | 92.5 | 92.5 |
| Cab Rear to Rear Axle | 80 | 80 | 100 | 118 | 100 | 118 | 100 |
| Top of Frame to Top of Cab (in.) | 54.4 | 54.4 | 54.4 | 54.4 | 58.4 | 58.4 | 54.4 |
| Rear Axle to End of Frame (in.) | 68.5 | 68.5 | 68.5 | 50.5 | 68.5 | 50.5 | 68.5 |
| Load Height (loaded) (in.) | 25.9 | 26.2 | 26.2 | 26.2 | 26 | 26 | 25.9 |
| Front Overhang (in.) | 34.6 | 34.6 | 34.6 | 34.6 | 34.6 | 34.6 | 34.6 |
| Estimated base Curb Weight (lbs.) | 4782/4898 | 5059/5173 | 5124/5235 | 5134/5245 | 5354/5460 | 5363/5467 | 4847/4960 |

Interior Dimensions

| | E-350 Super Duty® Cutaway (SRW) / (DRW) | E-450 Super Duty® Cutaway (DRW) |
|-------------------------------|---|---------------------------------|
| First row Head Room (in.) | 42 | 42 |
| First row Shoulder room (in.) | 68.1 | 68.1 |
| First row Hip Room (in.) | 65.6 | 65.6 |
| First row Leg Room (in.) | 40 | 40 |

Capacities: Passengers, Fuel

| | E-350 Super Duty® Cutaway (SRW) / (DRW) | E-450 Super Duty® Cutaway (DRW) |
|------------------------------|---|---------------------------------|
| Seating capacity (std./opt.) | 1,2 | 1,2 |
| Fuel capacity (gal.) | 40/55 | 40/55 |

Engine Specifications

| | | |
|--|---|---|
| Engine type | 5.4L Triton® 16-valve flex fuel V8 | 6.8L Triton® 20-valve V10 |
| Engine electronics | EEC-V computer | EEC-V computer |
| Displacement | 330 CID | 415 CID |
| Horsepower (SAE net@rpm) | 255@4,500 | 305@4,250 |
| Torque (lb.-ft. @rpm) | 350@2,500 | 420@3,250 |
| Compression ratio | 9.06:1 | 9.06:1 |
| Bore x stroke (in.) | 3.55x4.16 | 3.55x4.16 |
| Main bearings | 5-bearing | 6-bearing |
| Valvetrain | SOHC, 2 valves per cylinder | SOHC, 2 valves per cylinder |
| Valve lifters | Hydraulic roller finger | Hydraulic roller finger |
| Fuel delivery | Sequential multiport electronic fuel injection (SEFI) | Sequential multiport electronic fuel injection (SEFI) |
| Electronic throttle control (ETC) | Std | Std |
| Engine oil cooler | Std | Std |
| Recommended fuel | Unleaded regular | Unleaded regular |
| Exhaust | Stainless steel | Stainless steel |
| Transmission type | TorqShift® 5-speed automatic overdrive | TorqShift® 5-speed automatic overdrive |
| Engine block material | Cast iron | Cast iron |
| Cylinder head material | Aluminum | Aluminum |

Chassis Specifications

| | |
|------------------------------|--|
| Front suspension | Twin I-beam IFS with computer-selected coil springs and stabilizer bar |
| Rear suspension | Multileaf 2-stage leaf springs/solid axle and rear stabilizer bar (DRW only) |
| Front and rear shocks | Heavy-duty gas-pressurized |
| Brakes | Power 4-wheel disc anti-lock |
| Steering | Recirculating ball, power assisted |

Maximum Payloads

| CUTAWAY | Engine | GCWR | GVWR | Payload |
|----------------------------|--------|-------|-------|---------|
| E-350 (SRW) 138" Wheelbase | 5.4L | 13000 | 10050 | 5268 |
| E-350 (SRW) 138" Wheelbase | 6.8L | 18500 | 10050 | 5152 |
| E-350 (DRW) 138" Wheelbase | 5.4L | 13000 | 11500 | 6441 |
| E-350 (DRW) 138" Wheelbase | 6.8L | 18500 | 11500 | 6327 |
| E-350 (SRW) 158" Wheelbase | 5.4L | 13000 | 10500 | 5203 |
| E-350 (SRW) 158" Wheelbase | 6.8L | 18500 | 10500 | 5090 |
| E-350 (DRW) 158" Wheelbase | 5.4L | 13000 | 12500 | 7376 |
| E-350 (DRW) 158" Wheelbase | 6.8L | 18500 | 12500 | 7265 |
| E-350 (DRW) 176" Wheelbase | 5.4L | 13000 | 12500 | 7366 |
| E-350 (DRW) 176" Wheelbase | 6.8L | 18500 | 12500 | 7255 |
| E-450 (DRW) 158" Wheelbase | 5.4L | 14050 | 14000 | 8646 |
| E-450 (DRW) 158" Wheelbase | 6.8L | 22000 | 14500 | 9040 |
| E-450 (DRW) 176" Wheelbase | 5.4L | 14050 | 14000 | 8637 |
| E-450(DRW) 176" Wheelbase | 6.8L | 22000 | 14500 | 9033 |