

SPECIFICATIONS	Short Wheelbase	Middle Wheelbase		Long Wheelbase	Super Long Wheelbase	
	Hard Top	FRP Top	Soft Top	Hard Top	Pickup	
	STD	LX	STD	STD	LX	STD
	24V 4.5 litre (1FZ-FE)	24V 4.5 litre (1FZ-FE)	24V 4.5 litre (1FZ-FE)	24V 4.5 litre (1FZ-FE)	24V 4.5 litre (1FZ-FE) 4.2 litre Diesel (1HZ)	

DIMENSIONS & WEIGHTS

Overall length	mm.	4070	4360		4980	5275
Overall width	mm.	1690	1690		1690	1690
Overall height	mm.	1935	1980	1980	2115	1970
Wheelbase	mm.	2310	2600		2980	3180
Tread	Front	mm.	1435	1435	1435	1435
	Rear	mm.	1420	1420	1420	1420
Ground clearance	mm.	230	230		235	235
Kerb weight	kg.	1750-2045	1790-2100	1780-2060	2010-2400	1930-2265 ^G / 2040-2375 ^D
Gross vehicle weight	kg.	2600	2600		3200	3200

CHASSIS

Suspension	Front	Rigid axle, Coil springs				
	Rear	Rigid axle, Semi-elliptic leaf springs				
Brakes	Front / Rear	Ventilated discs / Drums				
Min. turning radius (tyres)	m.	5.4 / 5.8 (4WD)	5.9 / 6.3 (4WD)		6.7 / 7.1 (4WD)	7.1 / 7.5 (4WD)
Fuel tank capacity	liters	90	90		90 (+90 extra)	
Tyres		7.50R16-6PRLT	7.50R16-6PRLT		7.50R15-8PRLT	

ENGINES

Types		24V 4.5 litre (1FZ-FE)		4.2 litre Diesel (1HZ)
Piston displacement	cc.	4477		4164
Max. output (SAE net)	kW/rpm	165 / 4600		95 / 3800
Max. torque (SAE net)	Nm/rpm	387 / 3600		285 / 2200
Fuel system		Electronic fuel injection		Distribution type fuel injection

G: Gasoline engine model

D: Diesel engine model

● Addition of extra features may change figures in this chart.

● Toyota Motor Corporation reserves the right to alter any details of specifications and equipment without notice. Details of specifications and equipment are also subject to change to suit local conditions and requirements. Please inquire at your local dealer for details of any such changes that might be required for your area.

● Note: Vehicles pictured and specifications detailed in this catalogue may vary from models and equipment available in your area. Vehicle body colour might differ slightly from the printed photos in this catalogue.