

2021 GMC YUKON and YUKON XL SPECIFICATIONS

POWERTRAIN – 5.3L V8 (SLE/SLT/AT4)

Type: 5.3L V-8 VVT DI with Dynamic Fuel Management and Stop/Start

Bore & Stroke (in / mm): 3.78 x 3.62 / 96 x 92

Block & Cylinder Head Material: Cast aluminum

Valvetrain: Overhead valve, two valves per cylinder, variable valve timing

Fuel Delivery: Direct high-pressure fuel injection with Dynamic Fuel Management

Horsepower (hp / kW @ rpm): 355 / 265 @ 5600 (SAE certified)

Torque (lb-ft / Nm @ rpm): 383 / 519 @ 4100 (SAE certified)

POWERTRAIN – 6.2L V8 (Denali)

Type: 6.2L V-8 VVT DI with Dynamic Fuel Management and Stop/Start

Bore & Stroke (in / mm): 4.06 x 3.62 / 103.25 x 92

Block & Cylinder Head Material: Cast aluminum

Valvetrain: Overhead valve, two valves per cylinder, variable valve timing

Fuel Delivery: Direct high-pressure fuel injection with Dynamic Fuel Management

Horsepower (hp / kW @ rpm): 420 / 313 @ 5600 (SAE certified)

Torque (lb-ft / Nm @ rpm): 460 / 623 @ 4100 (SAE certified)

TRANSMISSION & AXLE

Type: Hydra-Matic 10L80 10-speed automatic

Final Drive Ratio: 3.23 (with all engines)

CHASSIS & SUSPENSION

Suspension: Independent coil spring with passive dampers – Standard on SLE, SLT
Independent coil spring with Magnetic Rid – Standard on AT4, Denali
Independent Air Ride Adaptive Suspension with Magnetic Ride Control – Available on AT4, Denali

Steering Type: Electric power-assisted rack-and-pinion

Brake Type:	Four-wheel disc with ABS; vented front and rear Duralife™ rotors
Wheel Size:	18-in aluminum – Standard SLE 20-in aluminum – Standard SLT, AT4, Denali; Available SLE 22-in aluminum - Available SLE, SLT, Denali
Tires:	P265/65R18 all-season P275/65R20 all-season P275/60R20 all-terrain (AT4) P275/50R22 all-season

EXTERIOR DIMENSIONS

	YUKON	YUKON XL
Wheelbase (in / mm):	120.9 / 3071	134.1 / 3407
Overall Length (in / mm):	210.0 / 5335	225.2 / 5721
Overall Width (in / mm):	81.0 / 2058	81.0 / 2058
Overall Height (in / mm):	76.5 / 1943	76.5 / 1943
Track (in / mm):	68.4 / 1737 (front) 68.1 / 1730 (rear)	68.5 / 1741 (front) 68.3 / 1734 (rear)
Turning Circle (ft):	18": 38.1 20": 39.7 22": 39.7	18": 42.3 20": 43.3 22": 43.3
Steering Ratio:	16.6:1	15.9:1
Steering Turns, Lock-to-Lock:	18": 3.5 20": 3.3 22": 3.3	18": 3.3 20": 3.2 22": 3.2

INTERIOR DIMENSIONS

	YUKON	YUKON XL
Headroom (in / mm):	42.3 / 1074 (first row) 38.9 / 988 (second row) 38.2 / 970 (third row)	42.3 / 1074 (first row) 38.9 / 988 (second row) 38.2 / 970 (third row)
Legroom (in / mm):	44.5 / 1131 (first row) 42.0 / 1068 (second row) 34.9 / 886 (third row)	44.5 / 1131 (first row) 42.0 / 1068 (second row) 36.7 / 933 (third row)
EPA Passenger Volume (cu ft / L):	168.3 / 4767	170.8 / 4838
Max Cargo Area[^] (cu ft / L):	122.9 / 3479 (behind first row) 72.6 / 2057 (behind second row) 25.5 / 722 (behind third row)	144.7 / 4097 (behind first row) 93.8 / 2657 (behind second row) 41.5 / 1175 (behind third row)

[^]Cargo and load capacity limited by weight and distribution.