



Armored Mercedes-Benz 5550

ALPINE ARMORING INC.

alpineco.com







GENERAL SPECIFICATIONS

VIN: WDDUG8CB1FA077204

MAKE: Mercedes Benz

MODEL: S550

YEAR: 2015

ENGINE: 4.7L V8 Biurbo Gasoline

POWER: 449 hp

TRANSMISSION: 7-Speed Driver Adaptive

COLOR: **Black**

INTERIOR: Black Leather

SEATING: 2 + 3

6,890 lbs. (3,125 kg) APPROX. WEIGHT:

OTHER SPECIFICATIONS

HEIGHT:

58.7 in.

(149 cm)

WIDTH:

84 in.

(212 cm)

LENGTH:

206 in.

(520 cm)

WHEELBASE:

124 in.

(316 cm)







Firewall

Ballistic steel lines the firewall and provides protection up front.

4-1



Roof is lined with ballistic steel at angle.





Floor

Floor is lined with ballistic steel to protect against mines and grenade blasts.

4-2

Doors

All doors are lined with ballistic steel.





Exhaust Protection

The exhaust is protected by a steel mesh to prevent sabotage.

4-3

Heavy-Duty Hinges

Custom hinges that will withstand the weight of the armored doors.





Overlaps

All doors and windows feature ballistic steel overlaps to keep shrapnel from angle shots from entering the cabin.

Wheel Wells

Front and rear wheel wells are lined with ballistic steel.





Glass Thickness

Minimum 39 mm thick glass/polycarbonate composite transparent armor.

5-1



Anti-Spall Layer

Inner-most anti-spall layer prevents glass and bullet fragments from penetrating into passenger cabin area.

5-2



Multi-Hit Protection

All windows are capable of sustaining multiple hits while providing protection to passengers.

5-3




Anchored Windows

All windows are anchored for additional protection from explosions.

5-4







P.A./Multi-Siren System

Located on the center console. The multi-siren features standard siren tones, volume adjustment, and a public address system.

6-1



Red/blue LED lights are mounted in the front grill and visor area.





Power Windows

The front two windows are powered and lower approximately 5-6 inches for documents pass-thru.

6-2

Battery Protection

The battery is encased in a ballistic steel box.





ECM Protection

Electronic control module is encased in a ballistic steel box.

6-3

Fuel Tank Protection

The fuel tank is encased in a ballistic steel box to protect against mines and grenades.





Special Door Overlaps

All doors and windows feature built in ballistic steel overlaps.

Undercarriage Protection

Ballistic steel to protect all undercarriage of vehicle.



























VIN: WDDUG8CB1FA077204















ALPINE ARMORING'S BALLISTIC CHART

(3)										no one protects you		
	S	SPECS			LEVELS				BULLETS			better"
WEAPONS	TYPE	CALIBER (nm)	CLASS	STANAG	UL	ALPINE	NU	CEN	MASS (II)	MATERIAL	VELOCITY	NUMBER OF SHOTS
4	38 Special	9 x 19	Hondgon	Ti-	1	A1	LILIA		8.00	ια	358 M/S	-
1 ST	.357 Magnum	9 x 33	Hendgun	-	2	A2	LIIA	81 & 83	10.20	159	430 W/S	, 🔾
	.44 Magnum	11 × 33	Handgun	II-	3	АЗ	IIA	84	15.60	TMC	440 M/5	, —
12	MPS	9 x 19	SMG	100	6	A4	IIIA	82	8.00	too	427 #/5	5 —
-	Shotgon	12 Gauge	Shotgun		384	Aŝ	IIA	562	28.30	SLUG	503 M/S	
- Total	Tokarev	7.62 x 25	Handgen	12	-	A5	IIIA	-	5.50	ter	488 M/S	
-	Koloshnikov (ML-47)	7.62 x 39	Asseult Rifle	100	-	A6	100	85	9.70	scu	732 4/5	
-	Kalashnikas (MK-47 Millory)	7.62 x 39 API BZ	Assoult Rifle	11	170	A7	-	85+	11.70	SCI	774 N/S	
PHI	M16/AR-15	5.56 x 45 MXTO \$2109 5.56 x 45 MXTO Bull	Assoult Rifle	1	7	A8	W	85	4.00	1001 2001	900 M/S 833 M/S	
	Winchester (308	7.62 x 51	Rifle	1	1	A9	OH.	85	10.90	ıca	810 M/S	
- market	Bernington 700 SPS	747×43 IF [30-06]	High-Power Rifle	111	588	A10	W	87-	10.80 8.40	AF.	869 M/S 930 M/S	5
	Dregumov	7.67 x 54R 837 MM	Sniper Rifle	II	1725	A11	IV+	87+	10.04	XCI	854 M/S	
		12.7 x 99	High Power Rifle	N	10	A12	-	1-1	45.00	a	908 M/S	
一方	50 Cel					AIE					Y08 N/S	



Underwriters Laboratory, 752

National Institute of Justice, 0108.01

European Standard

... NATO's Standard (STANAG 4569)

... Alpine Armoring's Certified Standard

Lead Core Copper Jacket Jacketed Soft Point LCC1

ISP

Lead Wad Cutter LWC LCSJ Lead Care Steel Jacket

Steel Core Copper Jacket SCCI

AP Armor Piercing

56. Shotgun Shots (5)11.4 cm Square Pattern (Corners & Center)

Shots (3) 11.4 cm Triangular Pattern

Minimum Measured Velocity

NU Rating .. Levels I, II, IIA, & IIIA (based on 1 of 2 required calibers of ballistic threat)







VEHICLE WARRANTY



