

"no one **protects you better.**"



Armored Land Rover Range Rover

ALPINE ARMORING INC.

alpineco.com

Table of Content	
Vehicle Specifications.	Page 3
Opaque Armor Details	.Page 4
Transparent Armor Details	Page 5
Additional Features	Page 6
Completed Vehicle Photos: Exterior	Page 7
Completed Vehicle Photos: Interior	Page 8
Ballistic Reference Chart	Page 9
Vehicle Warranty	Page 10





GENERAL SPECIFICATIONS

MAKE: LAND ROVER

MODEL: RANGE ROVER AUTOBIOGRAPHY

YEAR: NEW

ENGINE: 5.0 liter LR-V8 Supercharged Gas.

POWER: 510 hp @ 5,400 rpm

TRANSMISSION: 8-Speed Automatic

COLOR: **Clients Choice**

INTERIOR: Clients Choice

SEATING: 2 + 3

FINAL WEIGHT: 7,860 lb (3,565 kg) approximately

OTHER SPECIFICATIONS

HEIGHT:

73 in.

(185 cm)

WIDTH:

82 in.

(208 cm)

LENGTH:

197 in.

(500 cm)

WHEELBASE:

115 in.

(292 cm)





Firewall

Ballistic steel firewall provides protection up front.

4-1



Roof is lined with ballistic steel at angle.





Floor

Floor is lined with ballistic steel to protect against mines and grenade blasts.

4-2

Doors

All doors are made from ballistic steel.





Exhaust Protection

The exhaust is protected by a steel mesh to prevent sabotage.

4-3

Heavy-Duty Hinges

Custom hinges that will withstand the weight of the armored doors.





Overlaps

All doors and windows feature ballistic steel overlaps to keep shrapnel from angle shots from entering the cabin.

4-4


Wheel Wells

Front and rear wheel wells are lined with ballistic steel.










Glass Thickness

Minimum 40 mm thick glass/polycarbonate composite transparent armor.

5-1



Anti-Spall Layer

Inner-most anti-spall layer prevents glass and bullet fragments from penetrating into passenger cabin area.

5-2



Multi-Hit Protection

All windows are capable of sustaining multiple hits while providing protection to passengers.

5-3



Anchored Windows

All windows are anchored for additional protection from explosions.

5-4





P.A./Multi-Siren System

Located on the center console. The multi-siren features standard siren tones, volume adjustment, and a public address system.

6-1



A separate ballistic steel rear partition is built in, making it so the tailgate doesn't need to be armored.





Power Windows

The front windows are powered and lower approximately 5-6 inches.

6-2

Entertainment System

CD/DVD/AM/FM player installed (includes remote).





Emergency Lighting

Blue LED lights are mounted in the front grill and visor area.

6-3

Seat Controls

Easy access controls for adjusting each rear seat.





Fuel Tank Protection

The fuel tank is encased in a ballistic steel box to protect against mines and grenades.

6-4

Maximum Head Clearance

Complete door armoring, to allow maximum head room at door entrance.





* Tel:+1.703.471.0002 * Fax:+1.703.471.0202 * www.alpineco.com * sales@alpineco.com *



















































A	G	PEcc	LEVELS					BULLETS			"no one protects you better"	
WEAPONS	TYPE	PECS		CTANAC	UL	ALPINE	NIJ				VELOCITY	NUMBER OF SHOTS
	.38 Special	9 x 19	CLASS Handgun	STANAG	1	AT I	AII.II.I	CEN	MASS (9) 8.00	MATERIAL		-j -
	.357 Magnum	9 x 33	Handgun		2	A2	I.IIA	B1 & B3	10.20	JSP	430 M/S	j 👄
	.44 Magnum	11 x 33	Handgun	-	3	АЗ	IIIA	B4	15.60	LWC	440 M/S	j 🕕
170	MP5	9 x 19	SMG	-	6	A4	IIIA	B2	8.00	ιco	427 M/S	j —
	Shotgun	12 Gauge	Shotgun	1	3 & 4	Aã	IIIA	SG2	28.30	SLUG	503 M/s	3
	Tokarev	7.62 x 25	Handgun	-	-	A5	IIIA	-	5.50	LCSJ	488 M/S	5
-	Kalashnikov (AK-47)	7.62 x 39	Assault Rifle	-	-	A6		B5	9.70	2CC1	732 M/s	₁ —
-	Kalashnikov (AK-47 Military)	7.62 x 39 API BZ	Assault Rifle	-	-	A7	-	B5+	11.70	2CC1	7 74 M/s	
PATT	M16/AR-15	5.56 x 45 NATO SS109 5.56 x 45 NATO Ball	Assault Rifle	1	7	A8	IV	B5	4.00	rcc) 2cc1	900 M/s 833 M/s	
	Winchester .308	7.62 x 51	Rifle	-	7	A9	III	B6	10.90 10.80	ľŒĴ	810 M/s	
	Remington 700 SPS		High-Power Rifle Sniper Rifle		5 & 8	A10	IV	B7-	8.40	AP -	869 M/S 930 M/S	
	Dragunov	7.62 x 54R B32 API	High-Power Rifle	111	-	A11	IV+	B7+	10.04 45.00	2001	854 M/S	
- - 	50 Cal	12.7 x 99	mgir rower tarie	IV	10	A12	_		15.00	()	908 M/s	



UL Underwriters Laboratory, 752

NIJ National Institute of Justice, 0108.01

CEN European Standard

STANAG ... NATO's Standard (STANAG 4569)

ALPINE Alpine Armoring's Certified Standard

LCCJ Lead Core Copper Jacket

JSP Jacketed Soft Point LWC Lead Wad Cutter

LCSJ Lead Core Steel Jacket SCCJ Steel Core Copper Jacket

AP Armor Piercing

SG Shotgun

Shots (5) 11.4 cm Square Pattern (Corners & Center)

Shots (3) 11.4 cm Triangular Pattern

Velocity Minimum Measured Velocity

NIJ Rating .. Levels I, II, IIA, & IIIA (based on 1 of 2 required calibers of ballistic threat)









WARRANTY

LAND ROVER RANGE ROVER AUTOBIOGRAPHY

This vehicle, as proposed to the client, would be under Alpine Armoring's premium warranty covering all its armored parts and labor as well as all added accessories for one full year, effective the day of sale. Additional warranty for longer period is available upon request.

Alpine Armoring Inc. hereby honors this warranty, in the United States and worldwide, against any and all related manufacturer's defects, including parts and labor.

MANAGEMENT AUTHORIZED ALPINE ARMORING INC. HERNDON, VIRGINIA, USA

DATE ISSUED



